

THE **5**
PASSIVE
ON WALL



Speaker type	Time coherent 5¼ point-source coaxial
Principle	Vented
Passive Active	Passive
SPL	Calculated data 105 dB cont. / 108 dB peak
Frequency Range	Calculated data 90 Hz - 20 kHz / -3 dB
Efficiency	89 dB / 1W/m
Power handling	100 W
Impedance	8 Ω
Woofer	5¼"
Tweeter	1" soft dome
Directivity horizontal x vertical in Deg°	85° x 85°
Input terminal	One 4-conductor Phoenix 12 AWG (3,3 mm²)
Enclosure Gehäuse	MDF

Width	9,84" 250 mm
Height	15,75" 400 mm
Depth with plug	2,95" 75 mm
Depth with grille	3,19" 81 mm
Depth grille	0,24" 6 mm
Weight	8,82 lbs 4,0 kg
Finish	Matte black white glossy
Custom colour options	Genuine piano lacquer and matt lacquer: colour of choice, other finishes upon request
Shape customization	possible, upon request
Mounting	4 x wall brackets for horizontal and vertical installation, 2 through holes for direct wall or ceiling mounting, VESA 100 mounting points

THE5 PASSIVE ON WALL is supplied with a front cover as standard |

