

THE **6**
PASSIVE
NARROW



Speaker type	Time coherent 6,5" point-source coaxial
Principle	Vented
Passive Active	Passive
SPL	Measured data 111 dB cont. / 122 dB peak
Frequency Range	Measured data 110 Hz - 20 kHz / -3 dB
Sensitivity	93 dB / 1W/m
Power handling	200W
Impedance	8 Ω
Woofers	6,5"
Tweeter	1" soft dome
Directivity horizontal x vertical in Deg°	85° x 85°
Input terminal	One 4-conductor Phoenix 12 AWG (3,3 mm²)
Enclosure Gehäuse	MDF

Width	19,49" 495 mm
Height	7,09" 180 mm
Depth with plug	3,46" 88 mm
Depth with grille	3,7" 94 mm
Depth grille	0,24" 6 mm
Weight	10,58 lbs 4,8 kg
Finish	Matte black white glossy
Custom colour options	Genuine piano lacquer and matt lacquer: colour of choice, other finishes upon request
Shape customization	possible, upon request
Mounting	4 x wall brackets for horizontal and vertical installation + 2 through holes for direct wall or ceiling mounting

THE6 PASSIVE NARROW is supplied with a front cover as standard |



Technical modifications subject to change without further notice | Technische Änderungen vorbehalten