

Specifications

General Specifications

Product Name	AK PA10
Model	PAS11
Body Material	Aluminum & Silicone
Analog Inputs	Unbalanced (3.5mm) / Balanced (4.4mm)
Headphone Outputs	Unbalanced (3.5mm) / Balanced (4.4mm)
Input Max Level	Unbalanced 2Vrms / Balanced 4Vrms
Output Level	[Low Gain] Unbalanced 2.1Vrms / Balanced 4.2Vrms (Condition No Load) [High Gain] Unbalanced 3.1Vrms / Balanced 6.2Vrms (Condition No Load)
Dimensions	2.87"(73mm)[W] x 5.51"(140mm)[H] x 0.91"(23.3mm)[D]
Weight	11.46oz (325g)
Charging Port	USB C Type

※ Recommended Headphone Impedance : 16 ~ 300 Ω

Audio Specifications

Frequency	[Low Gain] ±0.2dB (Condition : 20Hz-20kHz) Unbalanced / Balanced
Response	[High Gain] ±0.06dB (Condition : 20Hz-20kHz) Unbalanced / Balanced
S/N	[Low Gain] 111dB @ 1kHz, Unbalanced / 115dB @ 1kHz, Balanced [High Gain] 114dB @ 1kHz, Unbalanced / 117dB @ 1kHz, Balanced
THD+N	[Low Gain] 0.0045% @1kHz, Unbalanced / 0.0015% @1kHz, Balanced [High Gain] 0.0027% @1kHz, Unbalanced / 0.0013% @1kHz, Balanced
Crosstalk	[Low Gain] -83dB @ 1kHz Unbalanced / -110dB @ 1kHz Balanced [High Gain] -83dB @ 1kHz Unbalanced / -110dB @ 1kHz Balanced
Output Impedance	3.5mm (1.1ohm) / 4.4mm(1.3ohm)
Memory	
Capacity	4,200mAh 3.8V Li-Polymer