



Specifications

Continuous Output Power (120V/240V AC)

200W RMS@8Ω
 320W RMS@4Ω
 450W RMS@2Ω
 650W RMS@8Ω (Bridge mode)
 950W RMS@4Ω (Bridge mode)

THD+N

THD+N: 0.008%

SNR

200W@8Ω/1KHz
 Gain 23dB: ≥113dB @A-wt
 Gain 29dB: ≥110dB @A-wt

Frequency Response

10-30KHz @8Ω: ±0.5dB

Crosstalk

200W@8Ω/1KHz: ≤-95dB

Input

RCA Unbalanced*1; XLR Balanced*1

Input Impedance

RCA Unbalanced: 10KΩ
 XLR Balanced: 10KΩ

200W@8Ω/1KHz Input Sensitivity

RCA Input GAIN:23dB: 2.65V
 RCA Input GAIN:29dB: 1.3V
 XLR Input GAIN:23dB: 5.2V
 XLR Input GAIN:29dB: 2.4V

Damping Factor

>600 @8Ω 1KHz

Weight

Net Weight: 18Kg
 Gross Weight: 21.5Kg

Dimensions

Width: 430mm
 Length: 310mm
 Height: 147mm

Packing List

Power Cable*1
 Trigger Cable*1
 User Manual*1