

Specifications

Continuous Output Power (120 V / 240 V AC)	180 W RMS per channel @ 8Ω 280 W RMS per channel @ 4Ω 500 W RMS @ 8Ω (Bridge Mode; 4Ω bridged not supported)
Amplifier Class	Class AB
THD+N (Total Harmonic Distortion + Noise)	0.003% @ 1 kHz
Signal-To-Noise Ratio (SNR)	≥115 dB (A-weighted)
Input Connectors	1 × XLR Balanced, 1 × RCA Unbalanced
Input Impedance	XLR Balanced: 10 kΩ RCA Unbalanced: 10 kΩ
Input Sensitivity (For 180 W @ 8Ω/1 kHz)	XLR Input, 23 dB Gain: 5.2 V XLR Input, 29 dB Gain: 2.6 V RCA Input, 23 dB Gain: 2.65 V RCA Input, 29 dB Gain: 1.3 V
Frequency Response (@1 W / 8Ω)	10 Hz – 30 kHz: ±0.5 dB
Crosstalk (@180 W / 8Ω / 1 kHz)	≤ -95 dB
Damping Factor (@8Ω / 1 kHz)	> 400
Power Requirements	100–120 V~ 60 Hz / 220–240 V~ 50 Hz, 1200 W max
Weight	Net: 15.9 kg Gross: 18.6 kg
Dimensions (W × D × H)	265× 388 × 119mm (W × D × H)
Accessories Included	Power Cord*1, Trigger Cable*1, User Manual*1