

Basic Parameters

Model	EVERSOLO DMP-A6 Gen 2
Display	6-inch LCD Touchscreen
Internal Memory	4GDDR4 +32G eMMC
DAC	ES 9038Q2M*2
Audio Processor	XMOS XU316
Op-amp Chip	OPA1642
Power Supply	Low Noise, High-Quality Linear Power Supply
Built-in SSD Slot	M.2 NVME 3.0 2280 Interface Protocol, Supports up to 4TB
USB-A Ports	USB3.0*2
Ethernet	RJ-45 (10/100/1000Mbps)
Wireless Network	WiFi 2.4G+5G Dual-Band
Music Playback and DAC Decoding	Supports up to Stereo DSD512, PCM 768KHz 32Bit, MQA Format
Music Services	TIDAL, Qobuz, HIGHRESAUDIO, Amazon Music, IDAGIO, Calm Radio, Internet Radio, TuneIn, Radio Paradise, Deezer, SoundCloud, Presto Music, Apple Music*...
Network Protocol	WebDAV, UPnP, NFS, SMB, Onedrive, Drop box, emby, Plex...
Streaming	Roon Ready, DLNA, TIDAL Connect...
Control Methods	Mobile App Control, Touchscreen Control, Tablet App Control, TRIGGER OUT, WOL

Audio Input and Output

Bluetooth Audio Input	Bluetooth BT5.0, Supports SBC/AAC
USB-B Audio Input	USB Audio Compatibility: Windows (10, 11), Mac, Android, iOS Supports up to Stereo DSD512, PCM 768KHz 32Bit, MQA Format
Optical/Coaxial Audio Input	Supports up to Stereo PCM 192KHz 24Bit, Dop64, MQA Format
HDMI ARC Input	Supports up to Stereo PCM 192KHz/24Bit
USB Audio Output	Supports up to Stereo DSD512 Native, PCM 768KHz 32Bit, MQA Format
HDMI Audio Output	DSD64 Native multichannel/PCM 192KHz multichannel raw output, up to 5.1
Optical/Coaxial Audio Output	Supports up to Stereo PCM 192KHz 24Bit, Dop64, MQA Format
Analog Audio Output	Pre-output: XLR (Balanced) + RCA(UnBalanced)

Audio Characteristics

XLR Output Audio Characteristics	Output Level: 5.2V Frequency Response: 20Hz~20KHz (± 0.15 dB) Dynamic Range: >128dB SNR: >128dB @A-wt
----------------------------------	---

THD+N: <0.00009% (-120dB)
Crosstalk: >-125dB

RCA Output Audio Characteristics

Output Level: 2.6V
Frequency Response: 20Hz~20KHz (±0.2dB)
Dynamic Range: >124dB
SNR: >124dB @A-wt
THD+N: <0.00011% (-119dB)
Crosstalk: >-124dB

Other Information

PSU	AC 110~240V 50/60Hz Max 0.35A
Rated Power	13W
Dimensions	L 187mm * W 270mm * H 90mm
Packing List	Power Cable*1, USB Data Cable*1, Trigger Cable*1, User Manual*1
