

Put away all

Basic Parameters		▼
Model	T10	
Size	365 mm x 310 mm x 88 mm (W x D x H)	
Chassis Material	Aluminium alloy	
Display	8.6" LCD Touchscreen	
Internal Memory	8G DDR5 + 64G eMMC	
Power Supply	Custom O-Type Toroidal Transformer	
System Clock	Femtosecond Clock	
Audio Clock	OCXO Clock system + Phase-Locked Loop Technology	
USB Ports	USB 3.0 * 2	
Ethernet	RJ-45 (10/100/1000/2500Mbps)	
Wi-Fi	Dual-band Wi-Fi 6 (2.4G + 5G)	
SFP Fiber Network	Supports Gigabit single-mode single-fiber and single-mode dual-fiber optical modules (SFP module not included)	
Playback & Decoding	Supports up to stereo DSD 512 and PCM 768kHz 32-bit	
Supported Music Formats	DSD (DSF, DFF, SACD ISO Support DST up to DSD512), MP3, APE, WAV, FLAC, AIF, AIFF, AAC, NRG, CUE	

Music Services	TIDAL, Qobuz, HIGHRESAUDIO, Amazon Music, IDAGIO, Calm Radio, Internet Radio, TuneIn, Radio, Paradise, Deezer, SoundCloud, Presto Music, Apple Music...
Streaming	Roon Ready, Spotify Connect Lossless, TIDAL Connect, Qobuz Connect, DLNA, and more...
Control Methods	On-screen Touch Control, Eversolo Control, and Remote Control
Supported Protocols	UPnP, NAS, SMB
Audio Characteristics	▼
Isolated USB Audio Output	Supports up to stereo DSD512 Native and PCM 768kHz 32-bit (only compatible with DACs that support the UAC standard).
Isolated IIS Audio Output	Supports 8 output mode options. Supports up to stereo DSD512 Native and PCM 768kHz 32-bit.
Coaxial Output	Supports up to stereo PCM 192kHz 24-bit and DoP64
Optical Output	Supports up to stereo PCM 192kHz 24-bit and DoP64
AES/EBU Output	Supports up to stereo PCM 192kHz 24-bit and DoP64
External Clock Input	Supports external 10MHz / 25MHz clock input with 50Ω / 75Ω impedance
Other Information	▼
Power Supply	AC 110~240V 50/60Hz Rated Power: 20W
Packing List	Power Cable*1, Remote Control*1, User Manual*1

Dimensions

L 365 mm x W 310 mm x H 88 mm
