

KLIPSCH RSM-800

FULL-RANGE 8" INDOOR/OUTDOOR
RESIDENTIAL SURFACE MOUNT LOUDSPEAKER

Klipsch®



MORE BASS, LESS SPACE WITH THE ALL-NEW TRACTRIX® HYPERFOLD PORT™

Klipsch is all about high efficiency, low distortion. Building upon that legacy, we're introducing the all-new patented Tractrix® Hyperfold Port™ engineered to extend port length for maximum bass power via proprietary five-step folded design. Its increased airflow eliminates chuffing and port noise while providing a greater dispersion pattern for larger coverage areas.

IPX5 RATED FOR RESIDENTIAL ENVIRONMENTS

Perfect for indoor and outdoor residential installations around the globe, the Klipsch RSM-800 is IPX5 Rated. Your clients will rest easy knowing their new speakers will be water-resistant and rainproof for the most challenging residential environments.

SET SCREWS ON GRILLE

The included set screws on each grille ensures a secure fit between the speaker and grille, while making sure the grilles stay on the enclosures regardless of the environment.

1" TITANIUM COMPRESSION DRIVER FOR EFFORTLESS, HIGH-CLARITY DETAIL

Klipsch outperforms the competition with our all-new 1" Titanium-loaded floating driver bridge with wide dispersion phase plug. Using our patented mumps technology, the RSM-800 gives any space extra-wide coverage while providing even and consistent energy for your project.

DUAL 5-WAY BINDING POST FOR VERSATILE INSTALLATION

The RSM-800 employs dual 5-way binding posts for versatile connection.

SPECIFICATIONS

FREQUENCY RESPONSE¹	52Hz-20kHz +/- 4dB, 44Hz -10dB
POWER HANDLING²	100 watts (21V) 50Hz-10kHz (400 watts peak)
CALC. MAX. CONT. OUTPUT³	109dB
SENSITIVITY⁴	92dB
COVERAGE	100° +/- 20° 1kHz-20kHz
DIRECTIVITY INDEX	7dB +/- 1.5dB 800Hz-20kHz
NOMINAL IMPEDANCE	8 ohms 4.2 ohms at 150Hz minimum
ACOUSTIC CROSSOVER	2kHz
TRANSDUCERS	8" woofer 1" titanium compression driver, on a K-1200M horn/tweeter bridge
ENCLOSURE MATERIAL	All Weather ABS Plastic, Paintable
IP RATING	IPX5
ENCLOSURE TUNING	Vented via 3 folded Tractrix ports
INPUT CONNECTORS	Dual 5-way binding post
DIMENSIONS [WITH BRACKET]	15.5"(394mm) x 12"(305mm) x 9.31"(237mm) [11.12"(283mm)]
WEIGHT	15.75 lbs (7.15kg)

¹ 1m, half space, anechoic

² AES standard, continuous pink noise 50Hz-10kHz, 6dB peaks

³ Calculated at 1m at power handling power input

⁴ SPL at 1m half space, anechoic with 2.83V pink noise input

