

Technical Specifications



Disc formats

- UHD Blu-ray, Blu-ray, Blu-ray 3D, DVD-Video, DVD-Audio, AVCHD, SACD, CD, Kodak Picture CD, CD-R/RW, DVD±R/RW, DVD±R DL, BD-R/RE

Outputs

- Analog Audio Output: 7.1 channel RCA, 2 channel RCA and Balanced XLR
- Digital Audio Output: Optical, Coaxial, HDMI
- HDMI audio: up to 7.1 channel /192kHz PCM, up to 5.1 channel DSD, Bitstream
- HDMI video: UHD 23.976/25/30/50/59.94/60hz, 1080 I/P, 720P, 576I/P, 480I/P, source direct.

Analog audio characteristics(2 Channel)

- Frequency Range: 20Hz ~ 50kHz (± 0.01 dB)
- Signal - to - noise ratio: ≥ 120 dB (RCA); ≥ 130 dB (XLR)
- Total Harmonic Distortion + Noise: $\leq 0.0005\%$
- Output Level: (RCA) ≤ 3 Vrms; (XLR) ≤ 6 Vrms
- Dynamic Range: ≥ 120 dB (RCA); ≥ 130 dB (XLR)
- Channel Separation: ≥ 110 dB (RCA); ≥ 130 dB (XLR)

Analog audio characteristics(7.1 Channel)

- Frequency Range: 20Hz ~ 50kHz (± 0.01 dB)
- Signal - to - noise ratio: ≥ 120 dB
- Total Harmonic Distortion + Noise: $\leq 0.0005\%$
- Output Level: ≤ 3 Vrms
- Dynamic Range: ≥ 120 dB
- Channel Separation: ≥ 110 dB

General specification

- Power supply: AC 110-120V ~ 50/60Hz / AC 220-240V ~ 50/60Hz
- Power consumption: < 40 W, Standby < 0.5 W
- Dimensions: 445 x 321 x 133 mm
- Weight: 15.4kg
- Operating Temperature: 5°C ~ 35°C (41°F ~ 95°F)
- Operating Humidity: 15% ~ 75%