


PACKAGE CONTENTS

- 1 **Suitcase:** High-strength ABS plastic suitcase with foam inserts and leather handle
- 2 **Two sets of earpads included:**
 - one ANGLED ALCANTARA®,
 - one LEATHER + ALCANTARA® DUO
- 3 **Cable options:**
 - Mini XLR to 4 PIN XLR Balanced Copper PCUHD
 - Mini XLR to 2.5 mm Balanced Copper PCUHD
 - Mini XLR to 3.5 mm Copper PCUHD
 - Mini XLR to 4.4 mm Balanced Copper PCUHD
 - Mini XLR to 6.3 mm Copper PCUHD
 - Mini XLR to 4 PIN XLR Balanced Silver Plated PCUHD
 - Mini XLR to 2.5 mm Balanced Silver Plated PCUHD
 - Mini XLR to 3.5 mm Silver Plated PCUHD
 - Mini XLR to 4.4 mm Balanced Silver Plated PCUHD
 - Mini XLR to 6.3 mm Silver Plated PCUHD



TECHNICAL SPECIFICATIONS

Driver Type	Rinaro Isodynamic Hybrid
Operating Principle	Open
Ear Coupling	Circumaural
Frequency Response	8 – 110,000 Hz
Impedance	32 Ω
Sensitivity	105 dB SPL at 1V, 1kHz
Maximum SPL	>130 dB
Total Harmonic Distortion (THD)	<0.05% (in the whole frequency range)
Frame Weight	385g

MZ3 DRIVER SPECIFICATIONS

PHYSICAL	
Geometrical Shape	Ovoid
Size	102 mm x 73 mm
Weight	82 g
Casing	Fiberglass infused ABS
DIAPHRAGM	
Type	Rinaro isoplanar® [MZ3]
Active Area	4650 mm ²
Weight	0.16 g
Acoustic Mass	10.7 kg / m ⁴
Lower Frequency Limit	8 Hz
Upper Frequency Limit	110,000 Hz
MAGNET	
Array Type	Isodynamic
Size	75 mm x 49 mm
Magnetic Flux	0.35 T