



MEZE AUDIO

SPECIFICATIONS

OVERVIEW

DRIVER TYPE	Rinaro Isodynamic Hybrid Array MZ6
OPERATING PRINCIPLE	Open-back
EAR COUPLING	Circumaural
FREQUENCY RANGE	4 Hz - 96 kHz
IMPEDANCE	55 Ω
SENSITIVITY	101 dB SPL/mW at 1 kHz
MAXIMUM SPL	>130 dB SPL
THD	<0.05%
WEIGHT	350 g (12.3 oz.) (without earpads)
INPUT CONNECTOR	Dual 3.5 mm TS Jack

MZ6 DRIVER

GEOMETRICAL SHAPE	Ovoid
SIZE	92 mm x 63 mm
DRIVER WEIGHT	73 g (2.5 oz.)
CASING	Fiberglass reinforced polymer
DIAPHRAGM TYPE	Rinaro Parus MZ6
ACTIVE AREA	3,507 mm ²
DIAPHRAGM WEIGHT	0.06 g
ACOUSTIC MASS	6.5 kg/m
LOWER FREQUENCY LIMIT	4 Hz
UPPER FREQUENCY LIMIT	96,000 kHz

PACKAGE CONTENTS



- Case: PC-ABS headphone hard case
- Cable: 2.5m braided Furukawa PCUHD copper cable with dual 3.5mm mono TS jacks to 6.3mm jack termination
- PU leather cable pouch