

## Warranty

In the unlikely event that there is a defect with this product, it is covered by the Monitor Audio manufacturer's warranty, provided that the product was supplied by an authorised Monitor Audio retailer.

For the period of cover please refer to the product page on our website at [monitoraudio.com](http://monitoraudio.com)

### Register your Creator Series speakers

to ensure the best possible product and customer support

Register your speakers using the QR code or visit [monitoraudio.com/registration](http://monitoraudio.com/registration)



## Specifications

Model Name	CIS	CIM	CIL	C2S	C2M	C2M+TX	C2M+CP
Sensitivity (2.83Vrms@1m, Installed)	84dB	86dB	88dB	84dB	86dB	86dB	87dB
Output Size	Ø 171 mm (6.34")	Ø 212 mm (8.38")	Ø 248 mm (9.34")	Ø 171 mm (6.34")	Ø 212 mm (8.38")	Ø 212 mm (8.38")	Ø 212 mm (8.38")
Mounting Depth	99 mm (3.92")	99 mm (3.92")	99 mm (3.92")	99 mm (3.92")	99 mm (3.92")	99 mm (3.92")	177.5 mm (6.98")
External Dimensions	Ø 201 x 103 mm (Ø 7.91" x 4.06")	Ø 242 x 103 mm (Ø 9.53" x 4.06")	Ø 278 x 103 mm (Ø 10.94" x 4.06")	Ø 201 x 103 mm (Ø 7.91" x 4.06")	Ø 242 x 103 mm (Ø 9.53" x 4.06")	Ø 242 x 103 mm (Ø 9.53" x 4.06")	Ø 242 x 181.5 mm (Ø 9.53" x 7.15")
Inc Grilles (Ø x D)	(Ø 7.91" x 4.06")	(Ø 7.91" x 4.06")	(Ø 7.91" x 4.06")	(Ø 7.91" x 4.06")	(Ø 7.91" x 4.06")	(Ø 7.91" x 4.06")	(Ø 9.12" x 7.15")
Recommended Amplifier Power (RMS into 8 Ohms, Music Signal)	25-100 W	35-130 W	40-150 W	35-130 W	40-150 W	40-150 W	35-130 W
Continuous Power Handling (RMS into Nominal Impedance, Crest Factor)	50 W	65 W	75 W	65 W	75 W	75 W	65 W
Nominal Impedance	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Minimum Impedance (20Hz to 20kHz)	6.6 Ohms @ 150 Hz	6.5 Ohms @ 150 Hz	6.4 Ohms @ 150 Hz	6.8 Ohms @ 150 Hz	6.6 Ohms @ 150 Hz	6.4 Ohms @ 150 Hz	6.4 Ohms @ 150 Hz
Drive Unit Complement	5" (127 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	7" (178 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	9" (229 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	5" (127 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	7" (178 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	7" (178 mm) RST II dual-coil mid-bass driver 2 x 1" (25 mm) C-CAM tweeter	7" (178 mm) RST II mid-bass driver 1" (25 mm) C-CAM tweeter
Frequency Response, Installed (-6dB)	40 Hz - 30 kHz	35 Hz - 30 kHz	30 Hz - 25 kHz	40 Hz - 30 kHz	35 Hz - 35 kHz	35 Hz - 30 kHz	70 Hz - 35 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	110dB	113dB	116dB	111dB	114dB	114dB	116dB
Channels	1	1	1	1	1	1 (Mono) 2 (Stereo)	1
System Format	2-Way	2-Way	2-Way	2-Way	2-Way	2-Way	2-Way
Bass Alignment	-	-	-	-	-	-	Sealed
Crossover Frequency	LF/HF: 3 kHz	LF/HF: 2 kHz	LF/HF: 2 kHz	LF/HF: 2.5 kHz	LF/HF: 2.5 kHz	LF/HF: 2.25 kHz	LF/HF: 2.5 kHz
Boundary Switch	-	-	-	On/Off	On/Off	On/Off	On/Off
MF Switch	-	-	-	-	-	-	-
HF Switch	-	-	-	-	-	-	-
Mono/Stereo Switch	-	-	-	-	-	-	-
Music/Movie Switch	-	-	-	-	-	-	-
Construction Material	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant
Weight	1.4 kg (3 lb 1 oz)	1.9 kg (4 lb 3 oz)	2.5 kg (5 lb 8 oz)	1.5 kg (3 lb 5 oz)	2 kg (4 lb 6 oz)	2 kg (4 lb 6 oz)	2.6 kg (5 lb 11 oz)
Pie-Construction bracket	CS-B	CM-B	CL-B	CS-B	CM-B	CM-B	CM-B
Back Box	CSM-BOX	CSM-BOX	CML-BOX	CSM-BOX	CSM-BOX	CSM-BOX	CSM-BOX

# Specifications

Model Name	W1M-E	W1M	W2M	W2M-CP	W3M
Sensitivity (2.83Vrms@1m, Installed)	84dB	87dB	87dB	87dB	88dB
Cutout Size	527 x 198 mm (20 3/4 x 7 13/16")	527 x 198 mm (20 3/4 x 7 13/16")	527 x 198 mm (20 3/4 x 7 13/16")	527 x 198 mm (20 3/4 x 7 13/16")	527 x 198 mm (20 3/4 x 7 13/16")
Mounting Depth	85 mm (3.35")	85 mm (3.35")	85 mm (3.35")	97 mm (3.81")	85 mm (3.35")
External Dimensions (H x W x D)	560 x 231 x 90 mm (22 1/8 x 9 1/8 x 3 5/16")	560 x 231 x 90 mm (22 1/8 x 9 1/8 x 3 5/16")	560 x 231 x 90 mm (22 1/8 x 9 1/8 x 3 5/16")	560 x 231 x 102 mm (22 1/8 x 9 1/8 x 4 1/16")	560 x 231 x 90 mm (22 1/8 x 9 1/8 x 3 5/16")
Recommended Amplifier Power (RMS into 8 Ohm, Music Signal)	25-100 W	30-110 W	45-180 W	40-150 W	60-225 W
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	50 W	75 W	120 W	100 W	150 W
Nominal Impedance (20Hz to 20kHz)	8 Ohms	6 Ohms	6 Ohms	6 Ohms	6 Ohms
Minimum Impedance (20Hz to 20kHz)	6.5 Ohms @ 200 Hz (6.2 Ohms @ 20 kHz)	4.8 Ohms @ 15 kHz (4.1 Ohms @ 15 kHz)	4.8 Ohms @ 1.4 kHz (4.1 Ohms @ 15 kHz)	4.8 Ohms @ 1.4 kHz (4.3 Ohms @ 15 kHz)	4.8 Ohms @ 150 Hz
Drive Unit Complement	5" (127 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	2 x 5" (127 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	2 x 5" (127 mm) C-CAM mid-bass driver 1" (25 mm) C-CAM tweeter	2 x 5" (127 mm) RST II bass driver 3" (76 mm) RST II midrange driver 1" (25 mm) C-CAM tweeter	2 x 5" (127 mm) RST III bass driver 3" (76 mm) RST II midrange driver 1" (25 mm) C-CAM tweeter
Frequency Response, Installed (-6dB)	30 Hz - 30 kHz	40 Hz - 30 kHz	40 Hz - 35 kHz	60 Hz - 35 kHz	45 Hz - 60 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	110dB	113dB	116dB	118dB	122dB
Channels	1	1	1	1	1
System Format	2-Way	2-Way	3-Way	3-Way	3-Way
Bass Alignment	N/A	N/A	N/A	Sealed	N/A
Crossover Frequency	L7/HF: 2.5 kHz	L7/HF: 2.75 kHz	L7/HF: 650 kHz MF/HF: 3 kHz	L7/HF: 550 kHz MF/HF: 3 kHz	L7/HF: 650 kHz MF/HF: 3.5 kHz
Boundary Switch	N/A	N/A	On/Off	On/Off	On/Off
MF Switch	N/A	N/A	N/A	N/A	-/0/+
HF Switch	N/A	N/A	-/0/+	-/0/+	-/0/+
Construction Material	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant
Weight	2.6 kg (5 lb 11 oz)	3.4 kg (7 lb 9 oz)	3.9 kg (8 lb 9 oz)	4.4 kg (9 lb 11 oz)	4.7 kg (10 lb 6 oz)
Pre-Construction bracket	WM-B	WM-B	WM-B	WM-B	WM-B
Back Box	WM-BOX	WM-BOX	WM-BOX	WM-BOX	WM-BOX

Model Name	C2L	C2L-TZX	C2L-CP	C3L	C3L-CP	C3L-A
Sensitivity (2.83Vrms@1m, Installed)	88dB	88dB	89dB	89dB	89dB	89dB
Cutout Size	Ø 248 mm (9 3/4")	Ø 248 mm (9 3/4")	Ø 248 mm (9 3/4")	Ø 248 mm (9 3/4")	Ø 248 mm (9 3/4")	Ø 248 mm (9 3/4")
Mounting Depth	99 mm (3.9")	99 mm (3.9")	177.5 mm (6.99")	157 mm (6.18")	177.5 mm (6.99")	157 mm (6.18")
External Dimensions (H x W x D)	Ø 278 x 103 mm (Ø 10 9/16 x 4 1/16")	Ø 278 x 103 mm (Ø 10 9/16 x 4 1/16")	Ø 278 x 181 mm (Ø 10 9/16 x 7 1/8")	Ø 278 x 181 mm (Ø 10 9/16 x 7 1/8")	Ø 278 x 181 mm (Ø 10 9/16 x 7 1/8")	Ø 278 x 181 mm (Ø 10 9/16 x 7 1/8")
Recommended Amplifier Power (RMS into 8 Ohm, Music Signal)	60-240 W (Mono)	60-240 W (Mono)	50-200 W (Mono)	60-225 W (Mono)	45-180 W (Mono)	60-225 W (Mono)
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	120 W (Mono)	240 W (Mono)	100 W (Mono)	150 W (Mono)	120 W (Mono)	150 W (Mono)
Nominal Impedance	8 Ohms	4 Ohms (Mono)	8 Ohms	6 Ohms	6 Ohms	6 Ohms
Minimum Impedance (20Hz to 20kHz)	6.4 Ohms @ 15 kHz	3.2 Ohms @ 15 kHz	6.6 Ohms @ 10 kHz	4.8 Ohms @ 2 kHz	4.9 Ohms @ 2 kHz	4.6 Ohms @ 2 kHz
Drive Unit Complement	9" (229 mm) RST II mid-bass driver 1 1/4" (32 mm) C-CAM tweeter	9" (229 mm) RST II dual-coil mid-bass driver 1 1/4" (32 mm) C-CAM tweeter	9" (229 mm) RST II mid-bass driver 1 1/4" (32 mm) C-CAM tweeter	9" (229 mm) RST II mid-bass driver 1 1/4" (32 mm) C-CAM tweeter	9" (229 mm) RST II mid-bass driver 1 1/4" (32 mm) C-CAM tweeter	9" (229 mm) RST III bass driver 4" (102 mm) IDC II midrange driver 1" (25 mm) IDC II tweeter
Frequency Response, Installed (-6dB)	30 Hz - 30 kHz	30 Hz - 30 kHz	75 Hz - 25 kHz	45 Hz - 35 kHz	80 Hz - 35 kHz	45 Hz - 35 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	117dB	(Mono) 117dB	120dB	119dB	122dB	119dB
Channels	1	1 (Mono)	1	1	1	1
System Format	2-Way	2-Way	3-Way	3-Way	3-Way	3-Way
Bass Alignment	On/Off	On/Off	Sealed	On/Off	Sealed	On/Off
Boundary Switch	On/Off	On/Off	On/Off	On/Off	On/Off	On/Off
MF Switch	-	-	-/0/+	-/0/+	-/0/+	-/0/+
HF Switch	-/0/+	-/0/+	-/0/+	-/0/+	-/0/+	-/0/+
Music/Movie Switch	-	Music/Movie	-	-	-	-
Mono/Stereo Switch	-	Mono/Stereo	-	-	-	-
Construction Material	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant	Mineral filled ABS plastic, RoHS2 Compliant
Weight	2.5 kg (5 lb 8 oz)	2.7 kg (6 lb)	3.3 kg (7 lb 5 oz)	5 kg (11 lb)	5.7 kg (12 lb 10 oz)	5.1 kg (11 lb 3 oz)
Pre-Construction bracket	CL-B	CL-B	CL-B	CL-B	CL-B	CL-B
Back Box	CML-BOX	CML-BOX	CML-BOX	CML-BOX	CML-BOX	CML-BOX