

GENERAL SPECIFICATIONS**OPT IN, OUTPUT**

THD (20 Hz – 20 kHz)	<0.0008 % at 4 V _{out}
Signal-to-Noise Ratio	>120 dB (1 kHz)
Frequency response	20 Hz - 20 kHz, no subwoofer (± 0.5 dB)
Output Impedance	360 ohms
Maximum output voltage	>4 V (ref. digital source)
Crosstalk	<130 dB at 1 kHz

COAX IN, OUTPUT

THD (20 Hz – 20 kHz)	<0.0008 % at 4 V _{out}
Signal-to-Noise Ratio	>120 dB (1 kHz)
Frequency response	20 Hz - 20 kHz, no subwoofer (± 0.5 dB)
Output Impedance	360 ohms
Maximum output voltage	>4 V (ref. digital source)
Crosstalk	<130 dB at 1 kHz

ANALOG IN, OUTPUT

THD (20 Hz – 20 kHz)	<0.008 % at 3.5 V _{out}
Signal-to-Noise Ratio	>100 dB (1 kHz)
Frequency response	20 Hz - 20 kHz, no subwoofer (± 0.5 dB)
Input impedance	28 kohms
Output Impedance	360 ohms
Maximum input signal	<2 V _{rms} (0.008% THD)
Maximum output voltage	>3.5 V (ref. analog source)
Crosstalk	<110 dB at 1 kHz

OPT IN, SUBWOOFER OUT

THD (50 Hz)	<0.008 % at 4.5 V _{out}
Signal-to-Noise Ratio	>100 dB (1 kHz)
Output Impedance	600 ohms
Maximum output voltage	>4.5 V (ref. digital source)

COAX IN, SUBWOOFER OUT

THD (50 Hz)	<0.008 % at 4.5 V _{out}
Signal-to-Noise Ratio	>100 dB (1 kHz)
Output Impedance	600 ohms
Maximum output voltage	>4.5 V (ref. digital source)

ANALOG IN, SUBWOOFER OUT

THD (50 Hz)	<0.01 % at 4.5 V _{out}
Signal-to-Noise Ratio	>100 dB (1 kHz)
Input impedance	28 kohms
Output impedance	600 ohms
Maximum input signal	2.0 V _{rms} (0.008 % THD)
Maximum output voltage	>4.5 V (ref. analog source)

DIMENSION AND WEIGHT

Gross dimensions (W x H x D)	230 x 150 x 370 mm
	(9 1/8 x 6 x 14 5/8 inches)
Net weight	1.3 kg (2.9 lbs)
Shipping weight	2.5 kg (5.5 lbs)

Manufactured under license from Dolby Laboratories. Dolby, Dolby Audio, and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation. Specifications are subject to change without notice. Check out www.NADelectronics.com for updated documentation or latest information about CI S2.