

Technical specifications

2MR



Model	Red	Blue	Bronze	Black	Black LVB 250	78	Mono
Output voltage at 1 kHz, 5 cm/sec.	5.5 mV	5.5 mV	5 mV	5 mV	5 mV	4 mV	4 mV
Tracking ability at 315 Hz	70 μ m	80 μ m	80 μ m	80 μ m	80 μ m	70 μ m	70 μ m
Compliance, dynamic, lateral	18 μ m/mN	18 μ m/mN	20 μ m/mN	20 μ m/mN	22 μ m/mN	22 μ m/mN	22 μ m/mN
Cantilever material	Aluminium	Aluminium	Aluminium	Aluminium	Boron	Aluminium	Aluminium
Stylus type	Elliptical	Nude Elliptical	Nude Fine Line	Nude Shibata	Nude Shibata	Spherical	Nude Spherical
Recommended tracking force	1.8 g	1.8 g	1.5 g	1.5 g	1.6 g	1.8 g	1.8 g
Load resistance	47 kOhm	47 kOhm	47 kOhm	47 kOhm	47 kOhm	47 kOhm	47 kOhm
Load capacitance	150 – 300 pF	150 – 300 pF	150 – 300 pF	150 – 300 pF	150 – 300 pF	150 – 300 pF	150 – 300 pF
Cartridge weight	6 g	6 g	6 g	6 g	6 g	6 g	6 g
Cartridge height	14 mm	14 mm	14 mm	14 mm	14 mm	14 mm	14 mm

All specs at recommended tracking force