No.36 Specifications:

Type:	Closed box, front firing woofer
Drive Unit:	15 in. (380mm) long throw, carbon fiber cone with inverted carbon fibre centre cap, die cast alloy chassis
Frequency Extension:	– 6 dB at 15Hz in Room
Dual Parametric EQ:	23-90Hz, +/– 4 db in 1/3 dB increments, filters separable by 10Hz minimum
Input Connectors:	HIGH LEVEL Neutrik SpeakOn, Low Level stereo RCA and XLR, LFE RCA, LFE XLR
Output Connectors:	HIGH LEVEL Neutrik SpeakOn, LFE RCA, LFE XLR, Line XLR, Line RCA
Power Output:	1000 watts (RMS) Ultra High-Current Power Supply
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class AB/D
Wireless Capability:	Yes - Use with REL AirShip Direct, Sold separately
Protection System Fully Electronic with SET-SAFE:	Yes
DC Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	8 Amp semi delay 230 volts operation 15 Amp semi delay 115 volts operation
Dimensions W x H x D, Inc. Feet:	Including feet and rear panel controls, 29 ¼" x 21.3" x 32 1/8" in., (743 x 541 x 816mm) Add 1.75 in (44.5mm) in depth when using high level connector
Net Weight:	202.5 lbs. (91.8 kg)
Shipping Weight:	233 lbs (105.7 kg)
Finish:	Piano Black Lacquer
Supplied Accessories Mains Lead:	Yes
Neutrik SpeakOn	Yes, 10 Meters (32'10") Nominal
Users Manual:	Yes
Remote Control:	Yes
Batteries (AAA x 2):	Yes
Allen Key (2.5mm):	Yes