

PL-1 Specifications

Type:	(2) Front-firing active woofers, (1) Rear-firing passive radiator
Drive Unit:	(2) 6.5in. (165mm) FibreAlloy cone, long-throw, steel chassis
Passive Unit:	10in. (250mm) FibreAlloy cone, steel chassis
Lower Frequency Response:	-6 dB at 31 Hz, in room
Input Connectors:	HIGH-LEVEL Neutrik SpeakOn, LOW-LEVEL RCA, LFE RCA
Gain Control Range:	80 dB
Power Output:	300 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Pure Class D™
Protection System:	Fully Electronic SET-SAFE
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	100-240 volts selectable
Fuse:	2.5A for 230V operation 5A for 120V operation
Dimensions (WHD):	20.6 x 19.4 x 5.7in. (522 x 492 x 144mm) add 1.5in. (39mm) depth for on wall bracket
Net Weight:	41.6lbs. (18.9 kg)
Finish:	Gloss Piano Black or Gloss White Lacquer
Supplied Accessories	
Mains Lead:	Yes, 90 degree to permit on wall mounting
Neutrik SpeakOn Interconnect:	Yes. 1.5m cable intended for use with AirShip Direct™ transmitter
User Manual:	Yes