

7 TECHNICAL SPECIFICATIONS

	Olympica I G3
System	2,0 way Vented Box
Loudspeakers	Tweeter: 1 x 1.1" (28 mm) — DAD™ Arrow Point extended frequency silk tweeter Midwoofer: 1 x 6,5" — Paper Cone, Copper cap
Crossover Points	2300 Hz
Frequency Response (-3dB)	57 — 40,000 Hz
Sensitivity @2V83	87,0 dB
Nominal Impedance	4,0 Ω
Recommended Amplifier Power	30 - 250 W
Product Dimensions (Width - Height - Depth) [mm]	210 x 370 x 370 With Stand: 320 x 1052 x 415
Product Dimensions (Width - Height - Depth) [in]	8.3 x 14.6 x 14.6 With Stand: 12.6 x 41.4 x 16.3
Dimensions with Packaging (Width - Height - Depth) [mm]	525 - 545 - 495
Dimensions with Packaging (Width - Height - Depth) [in]	20.7 - 21.5 - 19.5
Weight [Kg]	11,0 (27,2 stand included)
Weight [lb]	24.3 (60 stand included)
Packaging Weight [Kg]	27
Packaging Weight [lb]	59.5
Cabinet Construction	Lute Shaped Cabinet, crafted from wood and aluminum