

8 SPECIFICHE TECNICHE/ TECHNICAL SPECIFICATIONS/ TECHNISCHE DATEN/ SPÉCIFICATIONS TECHNIQUES

System	4.5 way, Midrange sealed box, Woofers vented box "Stealth Ultraflex" system
Loudspeakers	Super Tweeter: Ø 20 mm, silk dome with dedicated waveguide, High Power Neodymium, Extended Range Double Soft Dome. Tweeter: Ø 38 mm, silk dome with dedicated waveguide, High Power Neodymium, Extended Range Double Soft Dome. Midrange: Ø 165 mm, Dual Drive motor system with neodymium ring magnet. Woofer: 2 x Dual Drive Motor System Ø 220 mm
Crossover	230, 300, 1800, 5600 Hz. High End components, Phase Coherent Level 3
Frequency response	28 Hz – 40000 Hz
Sensitivity	91 dB SPL (2.83V/1 m)
Nominal impedance	4 ohm
Suggested amplifier power output	50W - 600W, undistorted signal
Dimensions (HxWxD)	1176 × 411 × 512 mm / each 46.3 × 16.2 × 20.1 in / each
Dimensions with Packaging	1340 × 570 × 740 mm / each 53.8 × 22.4 × 29.1 in / each
Weight (each)	62 kg – net weight / 136,7 lb – net weight
Packaging Weight (each)	84.5 kg / 186.3 lb
Packaging Content	1 Photo book 1 Manual 1 Warranty extension card 1 Cleaning Kit 2 Wire tensioner 8 Feet 8 Spike shoe 2 Bag with 8 screws 1 Allen key 2 Fabric dust guard