

System

2,0 way

Midwoofer front vented box

Loudspeakers

High-end quality drivers

Tweeter: 1,1" DAD™ Arrow Point extended frequency tweeter, Copper shorting ring

Midwoofer: 1× 5" Midwoofer, Aluminum demodulation ring

Crossover Points

2100 Hz

Frequency response

52 Hz - 40.000 Hz

Sensitivity

86 dB SPL (2.83 V/1m)

Nominal impedance

4 Ohm

Recommended power amplifier

30 W - 150 W

Product dimensions (HxWxD)

377 - 200 - 304 mm / each

14.8 - 7.87 - 11.97 in / each

687 - 355 - 406 mm (stand dimensions)

27.1 - 13.2 - 16 in (stand dimensions)

Dimensions with packaging (HxWxD)

500 - 555 - 405 mm

19,69 - 21,85 - 15,94 in

831 - 437 - 615 mm (stand)

32.72 - 17.20 - 24.21 in (stand)

Weight

8,4 kg / each

18.52 lb / each

6,50 kg (stand weight)

14.33 lb (stand weight)

Packaging weight

20 kg /one carton includes 2 speakers

44.1 lb / one carton includes 2 speakers

12 kg (stand)

26.46 lb (stand)

Cabinet

Lute shape

Wood

Leather

Concrete

Aluminum - Concrete - Iron Steel (stand)