

System

2,0 way

Midwoofer front vented box

Loudspeakers

High-end quality drivers

Tweeter: 1,1" DAD™ Arrow Point extended frequency tweeter, Copper shorting ring

Midwoofer: 1× 6,5" Midwoofer, Aluminum demodulation ring

Crossover Points

3100 Hz

Frequency response

42 Hz - 40.000 Hz

Sensitivity

87 dB SPL (2.83 V/1m)

Nominal impedance

4 Ohm

Recommended power amplifier

30 W - 200 W

Product dimensions (HxWxD)

414 - 227 - 355 mm / each

16.3 - 8.94 - 13.98 in / each

687 - 355 - 406 mm (stand dimensions)

27.1 - 13.2 - 16 in (stand dimensions)

Dimensions with packaging (HxWxD)

525 - 605 - 455 mm

20.67 - 23.82 - 17.91 in

831 - 437 - 615 mm (stand)

32.72 - 17.20 - 24.21 in (stand)

Weight

10,40 kg / each

22.93 lb / each

6,50 kg (stand weight)

14.33 lb (stand weight)

Packaging weight

23,4 kg / one carton includes 2 speakers

51.6 in / one carton includes 2 speakers

12 kg (stand)

26.46 lb (stand)

Cabinet

Lute shape

Wood

Leather

Concrete

Aluminum - Concrete - Iron Steel (stand)