Driver	All-new proprietary 8” long-throw driver with high-precision tuned overhung motor configuration with 8” passive radiator
Amplifier Class D	350W RMS @ 0,5% THD, 600 W @ 2% THD, 800 W maximal
Frequency Response: Overall	18 – 300 Hz
Frequency Response: (± 3 dB)	32 – 180 Hz
Low Pass Crossover	30 to 200 Hz low-pass crossover with a 12 dB/octave slope
Phase	0 to 180 degrees
Cabinet Design	High-gloss MDF
Magnet Structure	Dual ferrite magnet motor
Woofer	All-new proprietary 8” long-throw driver with high-precision tuned overhung motor configuration with 8” passive radiator
Voice Coil	2” diameter Voice Coil with high current 4-layer high-purity copper wire windings
Input	Unbalanced Stereo/LFE RCA input, Balanced Stereo/LFE XLR Input, 3,5 mm mini jack 12 V trigger input, 5 V / 1 A Power USB socket to power external Wireless Signal transmitting system Wi-Connect II
Output	Unbalanced Stereo/LFE RCA output for easy daisy chain, Balanced Stereo/ LFE XLR output for easy daisy chain, 3,5 mm mini jack trigger output with 5 seconds delay
Power Selector	Blue (power on) / Red (power standby) mode indicator LED
Finishes	Black
Dimensions (H/W/D) (includes feet and connectors)	30 cm x 29 cm x 29 cm
Weight (approx)	15 kg
Shipping Weight (approx)	20 kg